

Large Format Print Solutions ideal for Production, Display Graphics and In-house Print.

iPF8300S

you can

Call 0845 675 2244

The imagePROGRAF iPF8300S is a 44"/A0 large format printer which provides the perfect balance between quality, productivity and cost.

IPF8300S 44 INCH 2,400 X 1,200 DPI 8 COLOURS GLOSSY A0 IN 3 MINUTES

63.5 SQM/HR

160GB HDD

330 OR 700ML INK TANKS

> 30,720 NOZZLES

BORDERLESS PRINTING

> ECONOMY PRINTING

## Key features

- New LUCIA EX pigment ink system and improved image processing technology delivering:
  - Wider colour gamut
  - Smoother gradation, deeper dark tones and sharper blacks
  - Improved scratch resistance and reduced bronzing
  - Higher print registration accuracy for precise text and fine lines
- High speed, economical printing with new Fast mode
- Built in 160GB Hard Disk Drive enabling storage of large print jobs which are easily accessible direct from the printers LCD panel



- Borderless printing, so no need for offline trimming - saving time and money
- Selectable high capacity ink tanks can be changed during print job keeping you more productive
- Manage print costs and track ROI full accounting and job costing software included
- Economy mode for lower running costs reduces ink consumption
- Large, bright and easy to use LCD operation panel easy access to sophisticated functions
- Choice of printer driver settings tailored to suit expertise of user

- User friendly simple roll paper loading and control the print from the front
- Bundled with free of charge PosterArtist Lite poster creation software - makes it easy to produce professional looking posters
- Print plug-ins for MS Office, Photoshop and Digital Photo Professional:
  - 64 bit compatibility
  - Photoshop plug-in has been enhanced to include CMYK (as well as RGB)
- Gigabit Ethernet compatible enabling fast data transfer, even for data-heavy files or high volume print jobs





## Specifications: iPF8300S

Model Class Ink Type Maximum Print Resolution Installation	iPF8300S 44-inch Pigment ink ; LUCIA EX ; 8-color ink: MBK, BK, PC, C, PM, M, Y, GY 2400 x 1200dpi User installation
PRINTING SPEED (A0 ROLL)	
Plain Paper Coated Paper	0:57 (Fast Economy) 3:10 (Standard) 1:38 (Fast Economy)
Photo Glossy Paper	3:09 (Standard) 3:10 (Fast Economy) 4:50 (Standard)
PRINTER STAND	
Туре	Assembly type
DIMENSIONS, WEIGHT (Net) W x D x H (mm), (kg)	
Main unit, Printer Stand, and Basket	1,893 (W) x 975 (D) x 1144 (H) mm Weight: approx. 143 kg (including Roll Holder Set; excluding ink and print heads)
DIMENSIONS, WEIGHT (Packaged) W x D x H (mm), (kg)	
Main unit (pallet included) Printer Stand/Basket	2,080 x 1,060 x 867 mm, Weight: approx. 170 kg 1,795 x 863 x 363 mm, Weight: approx. 43 kg
POWER	
Input power Power consumption Power Save Mode	AC 100 - 240 V (50 - 60 Hz) Operation: 190 W or less
100 V - 120V 220 V - 240 V Power off (standby) Operational Environment	5 W or less 6 W or less 1 W or less Temperature: 15 - 30°C, Humidity: 10 - 80 % (Condensation free)
ACOUSTIC NOISE	
Acoustic pressure	Operation: 50dB (A), Standby: 35 dB (A) or less Operation: approx 6.8 Bels (A),
Acoustic power	Орегация. арргох 6.8 веть (А),
MEMORY	70/ MP
Standard memory	384 MB
PRINTER LANGUAGES	CARO (Carabia Araba a carabia)
Printer language	GARO (Graphic Arts language with Raster Operations)
OPERATION PANEL  Display	Large LCD
Languages	US-English, French, German, Italian, Spanish, Russian
HARD DISK	0.5% 4.50.50
	2.5" 160 GB
INTERFACE	
USB 2.0 Ethernet Protocol	Built-in 10base-T, 100base-TX, 1000base-T IPX/SPX SNMP HTTP, TCP/IP, AppleTalk
PRINT HEAD	
Model Type Head configuration Nozzle pitch Droplet size Head replacement	PF-05 Bubble-jet on demand 6 colours integrated type (2 print head) 1, 200 dpi x 2 4 pl per colour User replacement

INK TANK	
Model Colours Capacity	PFI-304: MBK, BK, PC, C, PM, M, Y, GY MBK, BK, PC, C, PM, M, Y, GY Starter use: 330 ml, Sales use: 700ml / 330 ml
CUTTER	
Model Type Replacement	CT-06 Rotary cutter User replacement
MEDIA HANDLING	
Roll paper Cut sheet Paper path switch (roll/cut sheet) Media types	One Roll, Front-loading, Front Output Front-loading, Front Output Manually switchable by user Plain and coated paper, technical paper, film, photographic paper, proofing paper, backlit, self adhesive, banner and sign, fine art printing material
MEDIA SIZE	
Media Core size	Internal diameter of roll core: 2" / 3" (Option)
MEDIA THICKNESS	
Roll paper	0.07 - 0.8 mm
MEDIA WIDTH	
Roll paper Cut sheet	254 - 1118.0 mm 203.2 - 1118.0 mm
MINIMUM PRINTABLE LENGTH	
	203.2 mm
MAXIMUM PRINTABLE LENGTH	
Roll paper Cut sheet	18 m (Varies according to the OS and application) 1.6 m
BORDERLESS PRINTING	
Media width	515 mm (JIS B2), 1, 030 mm (JIS B0), 594 mm (ISO A1), 841 mm (ISO A0), 10", 14", 17", 24", 36", 42", 44"
REGULATIONS	Electrical safety regulations
Germany Russia Other countries	TUV Gost-R (locally obtained) CB certification
ENVIRONMENT CERTIFICATIONS	
	ENERGY STAR WW, RoHS directive, IT ECO Declaration Europe, WEEE, ErP Lot 6 (Europe)
OPTION	
Media Take-up Unit Roll Holder Set (2-inch core spindle)	TU-06 RH2-44
CONSUMABLES	
Ink Tank Print Head Cutter Blade Maintenance Cartridge Some images are simulated for clarity of repr	PFI-304 (330 ml): MBK, BK, PC, C, PM, M, Y, GY PFI-704 (700 ml): MBK, BK, PC, C, PM, M, Y, GY PF-05 CT-06 MC-08 oduction. All data is based on Canon's standard testing methods.
This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ⊚: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	













Canon Europe canon-europe.com

English Edition © Canon Europa N.V., 2011 Canon (UK) Ltd Woodhatch Reigate, Surrey RH2 8BF

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

Tel: 01737 220000 Fax: 01737 220022 www.canon.co.uk Canon Ireland Arena Road, Sandyford Industrial Estate Dublin 18, Ireland

Tel: 01 2052400 Fax: 01 2958141 www.canon.ie

