

The SEAL 62 Ultra Series is the ultimate range of easy to use, first time roller laminators. Low-priced yet fully functional, either the 62 Ultra S or Ultra C are an ideal match for your wide-format printer when high quality professional graphics are required.

Capable of mounting, laminating and encapsulating prints up to 61" (1550 mm), the SEAL 62 Ultra Series provides a cost-effective finishing solution for both inkjet and photographic media. With easy to use controls and simplified material loading, these feature packed laminators will process the most popular substrates up to 1/2" wide.

The 62 Ultra Series focus on simplicity and affordability are great for businesses wishing to introduce application solutions to their customers or wishing to complement existing lamination facilities. With its sleek, attractive design, a SEAL 62 Ultra rolls anywhere it is needed, or stores neatly out of the way.

The 62 Ultra Series provides both a single-heated and cold model, both ideal for producing a wide variety of top quality applications:

Rigid Indoor Displays • Rigid Outdoor Displays • Flexible Indoor Displays • Floor Graphics • Backlit Displays • Pop-Up Displays

Ease of Use

- Simple touch pad control panel
- Quick reference guide on board for applications
- Adjustable speed dial for user control of settings
- One control knob for 8 nip settings from 0 to 1/2"
- Easy to clean silicon rollers prevent sticking of materials
- Auto-grip shafts for easy loading of materials and removal of release liners
- No special power requirements for plug and play
- Castors for easy mobility

Optimum Performance

- Maximum nip opening of 1/2" for processing of most popular substrates
- Foot control for hands-free operation and precise media/substrate feed
- 61" (1550 mm) working width covers majority of the inkjet market

Safety

- Safety system with emergency stops
- CE/ETL/CSA certified
- Anti-tip bars for increased stability

Special Features

62 Ultra S


- 3 temperature settings 125°F/50°C, 195°F/90°C, 250°F/120°C for use with different films and adhesives

62 Ultra C

- Maximum speed up to 10ft/minute



Flexible Nip Adjustment



Innovative 'Auto-grip' Shafts



Simple Control Panel

SEAL[®] 62 Ultra Series

SPECIFICATIONS



Release Liner Take-up (62 Ultra S & C)



Anti-tip Bar (62 Ultra S & C)



Back out-feed table (62 Ultra C only)

Specifications	SEAL 62 Ultra S	SEAL 62 Ultra C
Max. Working Width	61" (1550 mm)	61" (1550 mm)
Max. Diameter Supply Roll	6" (156 mm)	6" (156 mm)
Max. Speed	5 ft/min. (1.5 m/min.)	10 ft/min. (3 m/min.)
Max. Substrate Thickness	1/2" (12.5 mm)	1/2" (12.5 mm)
Max. Film Thickness	10 mil (top) / 10 mil (bottom)	5 mil (top) / 5 mil (bottom)
Max. Roller Temperature	250°F (120°C) (Top Roller)	N/A
Roller Heating	Single (Top)	None
Dimensions	Width: 76.3" (1940 mm) Depth: 22" (560 mm) Height: 43.7" (1110 mm)	Width: 76.3" (1940 mm) Depth: 22" (560 mm) Height: 43.7" (1110 mm)
Net Weight	311 lbs. (140 kg)	300 lbs. (136 kg)
Shipping Dimensions	Width: 81" (2060 mm) Depth: 24.8" (630 mm) Height: 28.4" (720 mm)	Width: 81" (2060 mm) Depth: 24.8" (630 mm) Height: 28.4" (720 mm)
Shipping Weight	416 lbs. (189 kg)	405 lbs. (184 kg)
Electrical Requirements	Single Phase 230 VAC, 50/60 Hz, 13A	Single Phase 115 VAC, 50/60 Hz, 1A
Safety Certification	cETLus, CE	cETLus, CE
Warranty	1 year parts (excluding rollers-180 days), 180 days labor (both models)	
Order Code	63062	63063

Neschen Americas
7091 Troy Hill Drive
Elkridge, MD 21075
Tel: 410-540-8900
Fax: 410-579-8960

Neschen Americas Canada
1601 Matheson Blvd. E.
Mississauga, Ontario
Canada, L4W 1H9
Tel: 905-212-9232
Fax: 905-212-9313

CE cETL



www.neschenamericas.com

Contact your local distributor: