

VERSACAMM VP-300 30" ECO-SOLVENT" INKJET PRINTER/CUTTER VERSACAMM VP-540 54" ECO-SOLVENT" INKJET PRINTER/CUTTER







Versa Power

INTRODUCING THE POWERFUL NEW VERSACAMM VP SERIES

Faster than a speeding locomotive. Able to wrap tall vehicles in a single bound. It's the VersaCAMM VP Series with VersaPower! VersaCAMM has become the most popular printer/cutter in the world, a hero to sign and graphic pros everywhere. Now, we've beefed it up in just about every category. It's faster, with enhanced print clarity and a host of advanced productivity tools like Roland Color. The improved media feed system provides greater print/cut performance during long production runs. And its rugged reliability is backed by our new two-year, trouble-free warranty.

When you need it fast, you need VersaPower. When you're surrounded by deadlines, you need VersaPower. When you need 200 labels, 6 banners and 20 t-shirts for the same project, you need VersaPower.

Want to be a superhero? VersaPower is here to save the day.





VERSACAMM® VP ECO-SOLVENT® INKJET PRINTER/CUTTERS



PRODUCT HIGHLIGHTS

- Integrated print/cut capabilities
- Photorealistic CMYK printing up to 1440 dpi
- Variable Droplet Technology for superb detail
- Max. print speeds up to 166 sqft./hr. (VP-540) and 124 sqft./hr. (VP-300)
- 54" Maximum media width (VP-540) 30" Maximum media width (VP-300)
- Advanced ECO-SOL MAX INK
 - > Available in 440 or 220 cc cartridges
 - > Bonds to both uncoated and coated media
 - > Vibrant water, scratch and UV resistant graphics
 - > 3-year outdoor durability without lamination*
 - > No special ventilation equipment required
- New Roland VersaWorks™ RIP software included
 - > Roland Color System
 - Variable Data Printing
- Automated Maintenance System
- Optional media take-up system supporting rolls up to 66.15 lbs (VP-540) and 44.1 lbs (VP-300)
- Two-Year Trouble-Free Warranty

		VERCACANA AVR 700	VERCACA A A VR F 40
SPECIFICATIONS		VERSACAMM VP-300	VERSACAMM VP-540
Print resolution		Maximum 1440 dpi	
Printing/cutting width		7-5/16 to 29 in. (185 to 736 mm)	7-5/16 to 53 in. (185 to 1346 mm)
Acceptable media width		8-5/16 to 30 in. (210 to 762 mm)	8-5/16 to 54 in. (210 to 1371 mm)
Ink cartridges	Type Capacity Color	Roland ECO-SOL MAX INK 4 cartridges: 220 cc ±5 cc or 440 cc ±5 cc Cyan, Magenta, Yellow, Black	
Printing/cutting speed		Maximum 124 sq. ft./hr / 11.8 ips	Maximum 166 sq. ft./hr / 11.8 ips
Cutting force/offset		30 to 200 gf / 0 to 1.5 mm	
Interface		Ethernet (10 BASE-T / 100 BASE-TX, automatic switching)	
Power-saving function		Automatic sleep feature	
Power supply		Maximum: 5.8 A (AC 100 to 120 V ±10% 50/60 Hz)	Maximum: 8.3 A (AC 100 to 120 V \pm 10% 50/60 Hz)
Dimensions (with stand)		66.9 [W] x 39.4 [D] x 44.3 [H] in. (1699 [W] x 1000 [D] x 1125 [H] mm)	90.9 [W] x 39.4 [D] x 44.3 [H] in. (2308 [W] x 1000 [D] x 1125 [H] mm)
Weight (with stand)		193 lb (87.5 kg)	240 lb (109 kg)
Environment	Power on Power off	Temperature: 59-90°F (15-32°C) (68°F+ recommended) Humidity: 35-80% (no condensation) Temperature: 41-104°F (5-40°C) Humidity: 20-80% (no condensation)	

^{*}Outdoor durability is based on accelerated weather tests. Results may vary depending upon location and application. Dry times vary depending on specific media characteristics. Lamination may be required for some applications or environmental conditions.



